

## **Quick start guide for RRS1100**

### **A. To set-up your new digital receiver:**

**1. Located on the right rear corner are two connectors.**

**Attach your antenna to the left connector (inside connector).**

**2. Locate antenna in a window or near an outside wall.**

**3. Make sure receiver is switched off (turn front knob to left), and then plug the unit into a standard electrical outlet.**

**4. Turn on the digital receiver via the knob on the front.**

**5. There will be a “ticking” sound for about 12 seconds.**

**The programs of your audio information service should follow.**

**6. If you do not hear the service programs, please use the following procedure to scan for the audio information service signal in your area (See instructions).**

## **Quick start guide for RRS1100 (continued)**

### **B. Scan instructions:**

- 1. Verify antenna is properly connected and oriented.**
- 2. Unplug digital receiver from electrical outlet.**
- 3. Turn on the knob on the front panel.**
- 4. Plug the digital receiver into the electrical outlet.**

**[This initiates the internal scan procedure for the audio information service in your area. The receiver will make a “ticking” sound every second for about 4 minutes indicating that the receiver is scanning.]**

- 5. After scanning is complete, the “ticking” sound will stop and the digital receiver will play your audio information service.**
- 6. If you do not hear the audio information service, try moving the antenna and repeat the scan procedure.**
- 7. If you still do not hear your audio information service, please contact your service provider.**